



0800 VANDA NZ
(0800 826 326)
Sales@vanda.co.nz
www.vanda.co.nz



Somfy Sonesse 40 3/28 Wire-Free Li-ion RTS



Specification	Details
Item Number/Code	VA.SMFY.3060 #1240486
Head Colour	White
Motor Length	655mm
Minimum Blind Width	730mm
Maximum Linked Blind Size	12.6 m ²
Lifting Capacity	9 kg
Nominal Torque	3.0 Nm
Nominal Speed	20 RPM (Adjustable 10-28)
Limit Switch Type	Electronic
Index Protection Rating	IP 30 (for indoor use only)
Sound Level	45 dBa (at nominal speed)
Battery Size/Type	2600mAH (Rechargeable Li-ion)
Power Supply	12V AC/DC Plug (#9028893)

Additional Accessories

- 12v Charger (USB-C Port)
- Direct Power Option (AC/DC plug) (#9028893)
- Solar Panel
- Remote control (1, 2, 5, 6 & 16 Channel)
- Motor head covers
- TaHoma switch

Sonessé 40 WF RTS
Ø40mm 3Nm WF Motor

A powerful, intuitive WireFree motor delivering optimum performance for a wide range of interior applications

PRODUCTS MAIN FUNCTIONALITIES



Somfy Radio Technology



WireFree
Simple and efficient installation



Designed for silence
Whisper Quiet operation



Powerful lifting capacity
3Nm (suitable for linked blinds)



'my' favourite
In one click move the blind to your favourite position

ADJUSTABLE SPEED

Adjustable speed
10-28 by increments of 2 rpm



Soft start, soft stop



Compatible with Connexoon Window RTS
for app & voice control



Inbuilt Lithium-ion battery with long battery life
(1 year per charge)



Compatible with WF Solar Panel



somfy®

COMPATIBLE END PRODUCTS



Roller Blinds



Roman Blinds



Pleated & Cellular



Zebra



Sheer



Venetian

BENEFITS FOR PROFESSIONALS

Powerful and versatile

- Dedicated to powering a wide range of interior applications (including linked blinds)
- Suitable for tubes 40mm in diameter

Easy installation

- Built in lithium Li-ion battery; no external batteries, no wires and no requirements for an electrician
- Programming button and LED on motor head interface
- Up and down end-limits set via transmitter

BENEFITS FOR END USERS

Daily comfort and convenience

- Whisper-quiet smooth operation
- Discreet design with no wires or external batteries

Easy to use and maintain

- Rechargeable battery
- Low battery LED indicator

Smart and simple

- Compatible with Connexoon Window RTS for app control or with Google Assistant and Amazon Alexa for voice control

TECHNICAL DATA

Voltage Supply	12V DC
Index Protection Rating	IP30 (for indoor use only)
Limit Switch Unit	Electronic
Temperature Working Range	0°C to +60°C
Temperature Storage Range	-20°C to +40°C
Insulation Class	Class III
Antenna	15cm wire length. Must not be cut or lengthened. For greatest RF range, it must not be exposed and should not come in to contact with metal surfaces. RF wire may need to be repositioned for optimal performance.

PERFORMANCE

Nominal Torque	3 Nm
Nominal Speed	20 rpm
Adjustable Speed	10-28 by increments of 2 rpm
Sound Level	< 45 dBa (at nominal speed)
Radio Protocol	RTS
Radio Frequency	433.42 MHz
Battery Lifetime	12 months*
Power Supply	Li-ion embedded battery
Low Battery Indicator	LED
Charging Time	8 hours
Item Number	1240486

* Based on 1.4m wide, 1.4m high 1 upward and 1 downward cycle per day.