

	Vanda
erior wall cladding	
ulation –	VANDA HOLDINGS LTD Unit G, 166 Marua Road Ellerslie, Auckland 0800 826 326 admin@vanda.co.nz www.vanda.co.nz
	PRODUCT : Vanda Flush Fit Single System Track VA.FF.0001
uminium joinery allow for flush fit tween door/window ad and bottom of sh box coordinate rusion with joinery unufacturer)	DESCRIPTION : The Flushfit aluminium track is designed flush to the ceiling with a minimal flange.
	MATERIAL : Powder coated aluminium in standard Vanda White or any Dulux powdercoat colour.
	NOTES : Vanda suggests the distances vary between 50-90mm. However the above measurements depend on the curtain heading being specifed. Ensure there is space for window/door handles.
	DISCLAIMER: Note that the architectural detail is shown for reference only. All architectural details shown shall not be used for construction, and shall be drawn by an architect according to the specific building project and application. Drawing intent shows the possible placement of Vanda products within a building context. 1:2 Scale (A3)
	CERTIFIED VILL SCORPERKG OF ALUMINIUM SCOPE 182. CKechnie
	*Full Life Cycle is 5.62kg of CQ.e perkg of Aluminium The Aluminium contained in our products has the above certification Authorised: VAN22700 Expiry: 30.11.2022